


耐熱線樣式說明 Heat Resistant Wire Specification Sheet

FEP鐵氟龍線 FEP Teflon insulation wire

導體:鍍錫銅絞線

Conductor: Tin-plated copper strand wire

額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+150°C
線規 Wire Gauge: 16/17/18/20/22/24/26/28 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -65~+200°C
線規 Wire Gauge: 10/12/14/16/18/20/22/24/26/28/30/32/36 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -80~+150°C
線規 Wire Gauge: 16/17/18/20/22/24/26/28 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+200°C
線規 Wire Gauge: 16/17/18/20/22/24/26/28 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+150°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: NO
溫度範圍 Temp. range: -80~+200°C
線規 Wire Gauge: 16/17/18/20/22/24/26/28 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -80~+200°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: NO
溫度範圍 Temp. range: -80~+200°C
線規 Wire Gauge: 16/17/18/20/22/24/26/28 AWG



額定電壓 Rated voltage: NO
溫度範圍 Temp. range: -60~+105°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -60~+150°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+200°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



PFA鐵氟龍線(PVC) PFA Teflon insulation wire

導體:鍍銀銅絞線

Conductor: silver-plated copper strand wire

額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+250°C
線規 Wire Gauge: 10/12/14/16/18/20/22/24/26/28/30/32/36 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -60~+200°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -80~+250°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+250°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG




額定電壓 Rated voltage: 150V
溫度範圍 Temp. range: -80~+250°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+200°C
線規 Wire Gauge: 16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+250°C
線規 Wire Gauge: 20/22/24/26/28/30/32 AWG



矽膠絕緣玻璃纖維電線 Silicone rubber Fiberglass weave wire

導體:鍍錫銅絞線

Conductor: Tin-plated copper strand wire

額定電壓 Rated voltage: 500V
溫度範圍 Temp. range: -60~+180°C
線規 Wire Gauge: 5/7/10/13/16/18/20 AWG



額定電壓 Rated voltage: 500V
溫度範圍 Temp. range: -60~+200°C
線規 Wire Gauge: 14/16/17/18/20/22/24 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -60~+150°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26/28/30 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -60~+150°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -60~+200°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -60~+200°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26 AWG



矽膠絕緣電線 Silicone rubber insulations wire

導體:鍍錫銅絞線

Conductor: Tin-plated copper strand wire

額定電壓 Rated voltage: 300V/ 500V
溫度範圍 Temp. range: -60~+200°C
線規 Wire Gauge: 8/10/12/16/18/20/22/26/27 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -60~+150°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 300V
溫度範圍 Temp. range: -60~+150°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 500V
溫度範圍 Temp. range: -60~+200°C
線規 Wire Gauge: 5/7/9/13/17 AWG



額定電壓 Rated voltage: 500V
溫度範圍 Temp. range: -60~+200°C
線規 Wire Gauge: 7/10/14/16/17/18 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -60~+150°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26 AWG



額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -60~+150°C
線規 Wire Gauge: 14/16/17/18/20/22/24/26 AWG



耐熱防火線300/500°C Fire-resistant wire

導體:裸銅、鍍銀銅絞線、純鎳絲絞線

Conductor: Nickel-plated copper strand wire

額定電壓 Rated voltage: 600V
溫度範圍 Temp. range: -80~+250°C
線規 Wire Gauge: 10/12/14/16/18/20/22/24/26/28/30/32/36 AWG

