



S.C.R. Controller 相位控制器



CRDA3M 80A
CRDA3M 100A
CRDA3M 125A



CRDA3M 160A
CRDA3M 200A



CRDA3M 250A
CRDA3M 300A
CRDA3M 500A

Order Information 訂單編號	Phase 相數	Series 系列	Load Voltage 額定電壓	Load Current 額定電流	Signal 信號	Option 選擇	Output Voltage 使用輸出電壓	Control Mode 控制方式	Ambient 使用週圍環境	Weight 重量 Kg	Dimension L : W : H
CRDA3M 220 080	3	3M	AC 220V	AC 80A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	3.6	245x125x155
CRDA3M 380 080	3	3M	AC 380V	AC 80A		F				3.6	245x125x155
CRDA3M 440 080	3	3M	AC 440V	AC 80A		F				3.6	245x125x155
CRDA3M 220 100	3	3M	AC 220V	AC 100A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	3.6	245x125x155
CRDA3M 380 100	3	3M	AC 380V	AC 100A		F				3.6	245x125x155
CRDA3M 440 100	3	3M	AC 440V	AC 100A		F				3.6	245x125x155
CRDA3M 220 125	3	3M	AC 220V	AC 125A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	4.3	310x125x155
CRDA3M 380 125	3	3M	AC 380V	AC 125A		F				4.3	310x125x155
CRDA3M 440 125	3	3M	AC 440V	AC 125A		F				4.3	310x125x155
CRDA3M 220 160	3	3M	AC 220V	AC 160A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	7.5	280x155x230
CRDA3M 380 160	3	3M	AC 380V	AC 160A		F				7.5	280x155x230
CRDA3M 440 160	3	3M	AC 440V	AC 160A		F				7.5	280x155x230
CRDA3M 220 200	3	3M	AC 220V	AC 200A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	13.5	345x155x230
CRDA3M 380 200	3	3M	AC 380V	AC 200A		F				13.5	345x155x230
CRDA3M 440 200	3	3M	AC 440V	AC 200A		F				13.5	345x155x230
CRDA3M 220 250	3	3M	AC 220V	AC 250A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	18.5	450x255x250
CRDA3M 380 250	3	3M	AC 380V	AC 250A		F				18.5	450x255x250
CRDA3M 440 250	3	3M	AC 440V	AC 250A		F				18.5	450x255x250
CRDA3M 220 300	3	3M	AC 220V	AC 300A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	19.0	450x255x250
CRDA3M 380 300	3	3M	AC 380V	AC 300A		F				19.0	450x255x250
CRDA3M 440 300	3	3M	AC 440V	AC 300A		F				19.0	450x255x250
CRDA3M 220 400	3	3M	AC 220V	AC 400A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	26.5	600x255x280
CRDA3M 380 400	3	3M	AC 380V	AC 400A		F				26.5	600x255x280
CRDA3M 440 400	3	3M	AC 440V	AC 400A		F				26.5	600x255x280
CRDA3M 220 500	3	3M	AC 220V	AC 500A	DC 4-20mA DC 1~5V	F	0~95%	Phase Angle	80% RH below 0~60 ℃	28.0	600x255x280
CRDA3M 380 500	3	3M	AC 380V	AC 500A		F				28.0	600x255x280
CRDA3M 440 500	3	3M	AC 440V	AC 500A		F				28.0	600x255x280
參考尺寸 Dimension											
	W 125 mm  155 mm 245 mm W 155 mm  230 mm 280 mm W 220 mm  240 mm 405 mm										