



SRDA3m 25A
SRDA3m 40A
(保險絲外加)



SRDA3m 25A
SRDA3m 40A
SRDA3m 50A



SRDA3m 50A
SRDA3m 63A
(保險絲外加)



SRDA3m 63A
SRDA3M 63A

Order Information 訂單編號	Phase 相數	Series 系列	Load Voltage 額定電壓	Load Current 額定電流	Signal 信號	Option 選擇	Output Voltage 使用輸出電壓	Control Mode 控制方式	Ambient 使用週圍環境	Weight 重量 Kg	Dimension L : W : H
SRDA3m 220 025	3	3m	AC 220V	AC 25A	DC 4-20mA DC 1~5V	2/3	0~100%	Zero Angle	80% RH below 0~60 °C	1.0	150x125x100
SRDA3m 380 025	3	3m	AC 380V	AC 25A		2/3				1.0	150x125x100
SRDA3m 440 025	3	3m	AC 440V	AC 25A		2/3				1.0	150x125x100
SRDA3m 220 025	3	3m	AC 220V	AC 25A	DC 4-20mA DC 1~5V	F.2/3	0~100%	Zero Angle	80% RH below 0~60 °C	1.6	215x125x100
SRDA3m 380 025	3	3m	AC 380V	AC 25A		F.2/3				1.6	215x125x100
SRDA3m 440 025	3	3m	AC 440V	AC 25A		F.2/3				1.6	215x125x100
SRDA3m 220 040	3	3m	AC 220V	AC 40A	DC 4-20mA DC 1~5V	2/3	0~100%	Zero Angle	80% RH below 0~60 °C	2.0	150x125x155
SRDA3m 380 040	3	3m	AC 380V	AC 40A		2/3				2.0	150x125x155
SRDA3m 440 040	3	3m	AC 440V	AC 40A		2/3				2.0	150x125x155
SRDA3m 220 040	3	3m	AC 220V	AC 40A	DC 4-20mA DC 1~5V	F.2/3	0~100%	Zero Angle	80% RH below 0~60 °C	1.6	215x125x100
SRDA3m 380 040	3	3m	AC 380V	AC 40A		F.2/3				1.6	215x125x100
SRDA3m 440 040	3	3m	AC 440V	AC 40A		F.2/3				1.6	215x125x100
SRDA3m 220 050	3	3m	AC 220V	AC 50A	DC 4-20mA DC 1~5V	2/3	0~100%	Zero Angle	80% RH below 0~60 °C	2.3	180x125x155
SRDA3m 380 050	3	3m	AC 380V	AC 50A		2/3				2.3	180x125x155
SRDA3m 440 050	3	3m	AC 440V	AC 50A		2/3				2.3	180x125x155
SRDA3m 220 050	3	3m	AC 220V	AC 50A	DC 4-20mA DC 1~5V	F.2/3	0~100%	Zero Angle	80% RH below 0~60 °C	3.0	215x125x155
SRDA3m 380 050	3	3m	AC 380V	AC 50A		F.2/3				3.0	215x125x155
SRDA3m 440 050	3	3m	AC 440V	AC 50A		F.2/3				3.0	215x125x155
SRDA3m 220 063	3	3m	AC 220V	AC 63A	DC 4-20mA DC 1~5V	2/3	0~100%	Zero Angle	80% RH below 0~60 °C	2.3	180x125x155
SRDA3m 380 063	3	3m	AC 380V	AC 63A		2/3				2.3	180x125x155
SRDA3m 440 063	3	3m	AC 440V	AC 63A		2/3				2.3	180x125x155
SRDA3m 220 063	3	3m	AC 220V	AC 63A	DC 4-20mA DC 1~5V	F.2/3	0~100%	Zero Angle	80% RH below 0~60 °C	3.2	245x125x155
SRDA3m 380 063	3	3m	AC 380V	AC 63A		F.2/3				3.2	245x125x155
SRDA3m 440 063	3	3m	AC 440V	AC 63A		F.2/3				3.2	245x125x155
SRDA3M 220 063	3	3M	AC 220V	AC 63A	DC 4-20mA DC 1~5V	F.2/3	0~100%	Zero Angle	80% RH below 0~60 °C	3.6	245x125x155
SRDA3M 380 063	3	3M	AC 380V	AC 63A		F.2/3				3.6	245x125x155
SRDA3M 440 063	3	3M	AC 440V	AC 63A		F.2/3				3.6	245x125x155
參考尺寸 Dimension	W 125 mm  150 mm W 125 mm  215 mm W 125 mm  180 mm W 125 mm  245 mm										
	100 mm  100 mm 100 mm  100 mm 155 mm  155 mm 155 mm  155 mm										