



SRDA1E



SRDA1B

Order Information 訂單編號	Phase 相數	Series 系列	Load Voltage 額定電壓	Load Current 額定電流	Signal 信號	Option 選擇	Output Voltage 使用輸出電壓	Control Mode 控制方式	Ambient 使用週圍環境	Weight 重量 Kg	Dimension L : W : H
SRDA1E 220 010	1	1E	AC 220V	AC 10A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	0.26	105x40x86
SRDA1E 220 025	1	1E	AC 220V	AC 25A						0.26	105x40x86
SRDA1E 220 040	1	1E	AC 220V	AC 40A						0.26	105x40x86
SRDA1E 220 070	1	1E	AC 220V	AC 70A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	0.26	105x40x86
SRDA1E 380 010	1	1E	AC 380V	AC 10A						0.26	105x40x86
SRDA1E 380 025	1	1E	AC 380V	AC 25A						0.26	105x40x86
SRDA1E 380 040	1	1E	AC 380V	AC 40A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	0.26	105x40x86
SRDA1E 380 070	1	1E	AC 380V	AC 70A						0.26	105x40x86
SRDA1E 440 010	1	1E	AC 440V	AC 10A						0.26	105x40x86
SRDA1E 440 025	1	1E	AC 440V	AC 25A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	0.26	105x40x86
SRDA1E 440 040	1	1E	AC 440V	AC 40A						0.26	105x40x86
SRDA1E 440 070	1	1E	AC 440V	AC 70A						0.26	105x40x86
SRDA1B 220 025	1	1B	AC 220V	AC 25A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	1.00	150x75x140
SRDA1B 220 040	1	1B	AC 220V	AC 40A						1.80	150x80x170
SRDA1B 220 060	1	1B	AC 220V	AC 60A						2.10	180x80x170
SRDA1B 220 080	1	1B	AC 220V	AC 80A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	2.40	210x80x170
SRDA1B 220 100	1	1B	AC 220V	AC 100A						2.60	250x80x170
SRDA1B 380 025	1	1B	AC 380V	AC 25A						1.00	150x75x140
SRDA1B 380 040	1	1B	AC 380V	AC 40A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	1.80	150x80x170
SRDA1B 380 060	1	1B	AC 380V	AC 60A						2.10	180x80x170
SRDA1B 380 080	1	1B	AC 380V	AC 80A						2.40	210x80x170
SRDA1B 380 100	1	1B	AC 380V	AC 100A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	2.60	250x80x170
SRDA1B 440 025	1	1B	AC 440V	AC 25A						1.00	150x75x140
SRDA1B 440 040	1	1B	AC 440V	AC 40A						1.80	150x80x170
SRDA1B 440 060	1	1B	AC 440V	AC 60A	DC 4-20mA DC 1~5V		0~100%	Zero Crossing	90% RH below -10~50 °C	2.10	180x80x170
SRDA1B 440 080	1	1B	AC 440V	AC 80A						2.40	210x80x170
SRDA1B 440 100	1	1B	AC 440V	AC 110A						2.60	250x80x170