

5 位 (0.8)單脈波/雙脈波轉速.線速.頻率(顯示/控制)錶(單段警報)

5 Digits (0.8) Micro-process RPM/ Linear-Speed/ Frequency Meter (1 Alarm)

產品編號 Model No.	an RP - 51 an RL - 51 an HZ - 51		an RP- 51 an RL- 51 an HZ- 51	
產品名稱 Product Name	轉速.線速.頻率顯示/控制錶 RPM/Linear-Speed/Frequency Display/Control Meter		轉速.線速.頻率顯示/控制錶 RPM/Linear-Speed/Frequency Display/Control Meter	
顯示方式 Readout Display	0~99999		0~99999	
輸入頻率 Input frequency	100KHz (50% Duty Cycle) x 1		100KHz (50% Duty Cycle) x 2	
輸出方式 Output Mode	(選配) 單組輸出 1 A.B接點 (Option) Single Alarm Output 1A.B Contact		(選配) 單組輸出 1 A.B接點 (Option) Single Alarm Output 1A.B Contact	
警報方式 Alarm Mode	(選配) 單段警報 AL 1 (Option) Single Alarm AL		(選配) 單段警報 AL 1 (Option) Single Alarm AL	
量測速度 Sampling Time	3次/秒 3 Cycles/Sec.		3次/秒 3 Cycles/Sec.	
量測精度 Accuracy	± 0.03% (全刻度) ± 0.03% Full Scale		± 0.03% (全刻度) ± 0.03% Full Scale	
使用電源 Power Supply	110V/220V/AC ± 10%		110V/220V/AC ± 10%	
零值調整 Zero Adjustment	無 None		無 None	
類比輸出 Analog Output	無 None		無 None	
消耗電力 Power Consumption	4.5 VA 以下 4.5 VA Below		4.5 VA 以下 4.5 VA Below	
接點容量 Relay Contact	AC 277V/7A, DC 30V/7A		AC 277V/7A, DC 30V/7A	
通訊方式 Comm. Mode	無 None		無 None	
通訊速率 Baud Rate	無 None		無 None	
環境溫度 Ambient Temperature	-10~60℃		-10~60℃	
環境溼度 Ambient Humidity	20~90 % RH		20~90 % RH	
過載指示 Over Range Indication	doFL/ioFL		doFL/ioFL	
絕緣耐壓 Surge Test	2 KVac / 1 min		2 KVac / 1 min	
外殼材料 Housing Material	A B S / PC (不自燃) Non-Flammable Case		A B S / P C (不自燃) Non-Flammable Case	
產品重量 Weight	00 Kg		00 Kg	
外觀尺寸 Size	96mm x 48mm		96mm x 48mm	
開孔尺寸 Panel Cutout	92mm x 45mm		92mm x 45mm	
接線圖 Connection Diagram				