

5 位(0.4)脈波轉速.線速.頻率.計數(顯示/控制) 單段警報

5 Digits Micro-process RPM/Linear Speed/Frequency/Counter with 1 Alarm

產品編號 Model No. 產品名稱 Product Name	an RP- 51 an RL- 51 an HZ- 51  轉速.線速.頻率(顯示/控制)單段警報 RPM/Linear Speed/Frequency with 1 Alarm	an C- -51 an C-1 51  計數器(顯示/控制)單段警報 Counter with 1 Alarm
顯示方式 Readout Display	0~99999	0~99999
輸入頻率 Input frequency	100KHz (50% duty cycle)	100KHz (50% duty cycle)
輸出方式 Output Mode	(選配) Relay A.B接點 0~99 sec. N/R/C/可設定 (Option) Relay A.B contact 0~99 sec. N/R/C/Can be set	(選配) Relay A.B接點 0~99 sec. N/R/C/可設定 (Option) Relay A.B contact 0~99 sec. N/R/C/Can be set
警報方式 Alarm Mode	(選配) 單組輸出 (Option) Single Alarm Output	(選配) 單組輸出 (Option) Single Alarm Output
量測速度 Sampling Time	10 cycles/sec(>10Hz) f cycles/sec(<10Hz)	10 cycles/sec(>10Hz) f cycles/sec(<10Hz)
量測精度 Accuracy	± 0.03% (全刻度) ± 0.03% Full Scale	± 0.03% (全刻度) ± 0.03% Full Scale
使用電源 Power Supply	AC/DC 100~240 V, DC 22~60 V	AC/DC 100~240 V, DC 22~60 V
零值調整 Zero Adjustment	無 None	無 None
類比輸出 Analog Output	無 None	無 None
消耗電力 Power Consumption	4.5 VA 以下 4.5 VA Below	4.5 VA 以下 4.5 VA Below
接點容量 Relay Contact	AC 277V/7A, DC 30V/7A	AC 277V/7A, DC 30V/7A
通訊方式 Comm. Mode	無 None	無 None
通訊速率 Baud Rate	無 None	無 None
環境溫度 Ambient Temperature	-10~60°C	-10~60°C
環境溼度 Ambient Humidity	20~90 % RH	20~90 % RH
過載指示 Over Range Indication	doFL/ioFL	doFL/ioFL
絕緣耐壓 Surge Test	2 KVac / 1 min	2 KVac / 1 min
外殼材料 Housing Material	A B S / PC (不自燃) Non-Flammable Case	A B S / PC (不自燃) Non-Flammable Case
產品重量 Weight	00 Kg	00 Kg
外觀尺寸 Size	48mm x 24mm	48mm x 24mm
開孔尺寸 Panel Cutout	45mm x 22mm	45mm x 22mm
接線圖 Connection Diagram		