

5 位 (0.8)RS-485通訊顯示/控制錶(二、四段警報)

5 Digits (0.8 LED) RS-485 Communication With 2 Alarms & 4 Alarms

產品編號 Model No.	an RS- 51	an RS- 51
產品名稱 Product Name	RS485錶顯示/控制二段警報 RS-485 meter with 2 Alarms	RS485錶顯示/控制四段警報 RS-485 meter with 4 Alarms
顯示方式 Readout Display	-19999~99999	-19999~99999
輸入信號 Input Signal	RS-485	RS-485
輸出方式 Output Mode	(選配) Relay 2A.B接點 0~99 sec. N/R/C/可設定 (Option) Relay 2A.B contact 0~99 sec. N/R/C/Can be set	(選配) Relay 4A 接點 0~99 sec. N/R/C/可設定 (Option) Relay 4A contact 0~99 sec. N/R/C/Can be set
警報方式 Alarm Mode	AL 1. AL 2	AL 1. AL2. AL3. AL 4
輸出解析 Output Resolution	15 bit 數位轉類比 15 bit digital to analog	15 bit 數位轉類比 15 bit digital to analog
量測精度 Accuracy	± 0.1 % (全刻度) ± 0.1 % Full Scale	± 0.1 % (全刻度) ± 0.1 % Full Scale
使用電源 Power Supply	AC/DC 100~240V, DC 12/24/30~90V	AC/DC 100~240V, DC 12/24/30~90V
零值調整 Zero Adjustment	無 None	無 None
類比輸出 Analog Output	(選配) (Option) 4~20mA. 0~10V. Option	(選配) (Option) 4~20mA. 0~10V. Option
消耗電力 Power Consumption	8.5 VA 以下 8.5 VA Below	8.5 VA 以下 8.5 VA Below
接點容量 Relay Contact	AC 277V/7A, DC30V/7A	AC 277V/7A, DC30V/7A
通訊方式 Comm. Mode	RS-485 Modbus RTU Mode	RS-485 Modbus RTU Mode
通訊速率 Baud Rate	19200/9600/4800/2400 bps	19200/9600/4800/2400 bps
環境溫度 Ambient Temperature	-10~60℃	-10~60℃
環境溼度 Ambient Humidity	20~90 % RH	20~90 % RH
過載指示 Over Range Indication	無 None	無 None
絕緣耐壓 Surge Test	1.5 KVac / 1 min	1.5 KVac / 1 min
外殼材料 Housing Material	A B S / PC (不自燃) Non-Flammable Case	A B S / PC (不自燃) Non-Flammable Case
產品重量 Weight	00 Kg	00 Kg
外觀尺寸 Size	96mm x 48mm	96mm x 48mm
開孔尺寸 Panel Cutout	92mm x 45mm	92mm x 45mm
接線圖 Connection Diagram		