

型號 <i>Model</i>	<i>AT 953A-4</i>	<i>AT 853A-4</i>	<i>AT 753A-4</i>	<i>AT 653A-4</i>	<i>AT 453A-4</i>
外觀 <i>Appearance</i>					
功能 <i>Function</i>	預設定計時器, 程序計時, 5組輸出, 4組位移規劃, (選配) <i>Preset Counter, Procedure Time Count, 5 Outputs, 4 Sets Displacement Setting (Selectable)</i>				
設定範圍 <i>Setting Range</i>	5組獨立各別設定, 第1組為主輸出, 4組位移規劃, 設定位數 (紅色 LED) 4位數 <i>5 Independent Specific Setting, First Setting for Main Output, Setting Digits (Red LED) 4 Digits</i>				
顯示範圍 <i>Display Range</i>	4位數 (紅色 LED) <i>4 Digits (Red LED)</i>				
計時方式 <i>Counting Mode</i>	1. 小時.分鐘, 2. 分鐘.秒數, 3. 計時, 4. 計分, 5. 計秒, 正算, 倒算 <i>1. Hour.Min, 2. Min.Sec., 3. Time, 4. Min, 5. Sec. Direct Count, Reverse Count</i>				
復歸方式 <i>Reset Mode</i>	手動復歸, 外部復歸, 自動復歸, 暫停計時 <i>Manual, External, Automatically Reset, Pause Time</i>				
輸入方式 <i>Input Mode</i>	手動按鍵輸入 <i>Manual Button Input</i>				
輸出方式 <i>Output Mode</i>	1. Relay output AC 220V/5A, 1A, 2. NPN output DC 24V/20mA. 3. 正動作輸出, 逆動作可規劃, 5組輸出 3. <i>Direct Action, Reverse Action Setting, 5 Outputs</i>				
工作電壓 <i>Operating Voltage</i>	90V ~ 240V / AC				
消耗電流 <i>Current Consumption</i>	Relay output 5W NPN output 4W				
停電記憶 <i>Memory Mode</i>	E^2 prom memory time:10 Years				
使用環境溫濕度 <i>Ambient Temp. & Humidity</i>	-10 ~ 60°C 80% RH Below				
振動測試 <i>Vibration Test</i>	0.7mm 20Hz. 500m/s ² X.Y.Z Each ten minutes				
外用電源 <i>Power Supply</i>	DC 24V±10% 50mA				
重量 <i>Weight ; Approx.</i>	g g g				
外觀尺寸 (單位: mm) <i>Dimensions (Units: mm)</i>	PANEL CUTOUT 開孔尺寸 92mm x 92mm 68mm x 68mm 92mm x 45mm 45mm x 92mm 45mm x 45mm				