

型號 Model	YJ2A50		YJ2A51		
外觀 Appearance					
顯示器 Display	3 1/2 位液晶顯示器,最大指示1999 3 1/2 Digits LCD Readings With Max. Value 1999		3 1/2 位液晶顯示器,最大指示1999 3 1/2 Digits LCD Readings With Max. Value 1999		
電源供應 Battery	9V電池 9V Battery (NEDA 1604, IEC 6F22, JIS 006P)		9V電池 9V Battery (NEDA 1604, IEC 6F22, JIS 006P)		
光譜回應波長範圍 Range mark	400~700 nm		400~700 nm		
峰值波長 Peak wavelength	550 nm		550 nm		
測試檔位 Range	200/2000/20000 Lux 20/200/2000 FC		200/2000/20000/200000 Lux 20/200/2000/20000 FC		
測試範圍 Range scale	0.1 ~ 19990 Lux 0.01 ~ 1999 FC		0.1 ~ 199900 Lux 0.01 ~ 19990 FC		
測試單位 Units of Measurement	Lux及FC (Foot-Candle); 1 FC=10.76 Lux		Lux及FC (Foot-Candle); 1 FC=10.76 Lux		
操作溫溼度 Operating Temp.& Humidity	0°C ~ 60°C / 低於80% R.H.(不結霜) 0°C ~ 60°C / Below 80% R.H.(No condensation)		0°C ~ 60°C / 低於80% R.H.(不結霜) 0°C ~ 60°C / Below 80% R.H.(No condensation)		
儲存溫溼度 Store Temp.& Humidity	-10°C ~ 60°C / 低於70% R.H.(不結霜) -10°C ~ 60°C / Below 70% R.H.(No condensation)		-10°C ~ 60°C / 低於70% R.H.(不結霜) -10°C ~ 60°C / Below 70% R.H.(No condensation)		
外接端子 External connection	無		3.5 Ø mm電壓輸出座,可接3芯同軸插頭,電壓輸出值 DC 1mV/ digit (最大值DC 2V/F.S.,輸出與本體電壓誤差為±0.5% rdg) DC Jack Output (I.D. Ø 3.5 mm) : DC 1mV/ digit (Max.) DC 2V/F.S., Accuracy is ± 0.5% rdg compare with meter's output.		
重量 Weight	約 270 g (含電池) Approx. 270g (including battery)		約 270 g (含電池) Approx. 270g (including battery)		
讀值準確度 Accuracy (23 ± 5 °C)	Model	Lux	準確度 Accuracy	FC	準確度 Accuracy
	YJ2A50	200	± (4% rdg + 5 dgt)	20	± (4% rdg + 5 dgt)
		2000	± (4% rdg + 5 dgt)	200	± (4% rdg + 5 dgt)
	YJ2A51	20000	± (5% rdg + 4 dgt)	2000	± (5% rdg + 4 dgt)
200000		± (5% rdg + 4 dgt)	20000	± (5% rdg + 4 dgt)	
外觀尺寸 (單位: mm) Dimensions (Units: mm)					