



CRDA3.J.K.L



CRDA3N

Order Information 订单编号	Phase 相数	Series 系列	Load Voltage 额定电压	Load Current 额定电流	S.C.R. Current 模块电流	Signal 信号	Option 选择	Output Voltage 使用 输出电压	Control Mode 控制方式	Ambient 使用 周围环境	Weight 重量 Kg	Dimension L : W : H
CRDA3 J 220 020	3	3J	AC 220V	AC 20A	25A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	5.70	350x180x150
CRDA3 J 220 030	3	3J	AC 220V	AC 30A	25A						5.80	350x180x150
CRDA3 J 220 040	3	3J	AC 220V	AC 40A	55A						5.90	350x180x150
CRDA3K 220 060	3	3K	AC 220V	AC 60A	55A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	6.20	410x200x170
CRDA3K 220 080	3	3K	AC 220V	AC 80A	90A						9.20	410x200x170
CRDA3L 220 100	3	3L	AC 220V	AC 100A	90A						13.00	450x255x190
CRDA3L 220 120	3	3L	AC 220V	AC 120A	110A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	14.00	450x255x190
CRDA3L 220 160	3	3L	AC 220V	AC 160A	160A						15.00	450x255x190
CRDA3N 220 200	3	3N	AC 220V	AC 200A	250A						0.00	0.00
CRDA3N 220 300	3	3N	AC 220V	AC 300A	250A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	0.00	0.00
CRDA3N 220 500	3	3N	AC 220V	AC 500A	450A						0.00	0.00
CRDA3 J 380 020	3	3J	AC 380V	AC 20A	25A						5.70	350x180x150
CRDA3 J 380 030	3	3J	AC 380V	AC 30A	25A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	5.80	350x180x150
CRDA3 J 380 040	3	3J	AC 380V	AC 40A	55A						5.90	350x180x150
CRDA3K 380 060	3	3K	AC 380V	AC 60A	55A						6.20	410x200x170
CRDA3K 380 080	3	3K	AC 380V	AC 80A	90A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	9.20	410x200x170
CRDA3L 380 100	3	3L	AC 380V	AC 100A	90A						13.00	450x255x190
CRDA3L 380 120	3	3L	AC 380V	AC 120A	110A						14.00	450x255x190
CRDA3L 380 160	3	3L	AC 380V	AC 160A	160A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	15.00	450x255x190
CRDA3N 380 200	3	3N	AC 380V	AC 200A	250A						0.00	0.00
CRDA3N 380 300	3	3N	AC 380V	AC 300A	250A						0.00	0.00
CRDA3N 380 500	3	3N	AC 380V	AC 500A	450A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	0.00	0.00
CRDA3 J 440 020	3	3J	AC 440V	AC 20A	25A						5.70	350x180x150
CRDA3 J 440 030	3	3J	AC 440V	AC 30A	25A						5.80	350x180x150
CRDA3 J 440 040	3	3J	AC 440V	AC 40A	55A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	5.90	350x180x150
CRDA3K 440 060	3	3K	AC 440V	AC 60A	550A						6.20	410x200x170
CRDA3K 440 080	3	3K	AC 440V	AC 80A	900A						9.20	410x200x170
CRDA3L 440 100	3	3L	AC 440V	AC 100A	110A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	13.00	450x255x190
CRDA3L 440 120	3	3L	AC 440V	AC 120A	110A						14.00	450x255x190
CRDA3L 440 160	3	3L	AC 440V	AC 160A	160A						15.00	450x255x190
CRDA3N 440 200	3	3N	AC 440V	AC 200A	250A	DC 4-20mA DC 1~5V		0~95%	Phase Angle	90% RH below -10~50℃	0.00	0.00
CRDA3N 440 300	3	3N	AC 440V	AC 300A	250A						0.00	0.00
CRDA3N 440 500	3	3N	AC 440V	AC 500A	450A						0.00	0.00