

型 号 <i>Model</i>		<i>P2085002</i> <i>P1084501</i>	<i>P2125004</i> <i>P1124502</i>	<i>P2185008</i> <i>P1184505</i>	<i>P2305015</i> <i>P1304510</i>
外 观 <i>Appearance</i>					
输 出 方 式 <i>Output Control</i>	<i>DC type-NPN NO</i>	★	★	★	★
	<i>DC type-NPN NC</i>	★	★	★	★
	<i>DC type-PNP NO</i>	★	★	★	★
	<i>DC type-PNP NC</i>	★	★	★	★
	<i>AC type 2 wires NO</i>	★	★	★	★
	<i>AC type 2 wires NC</i>	★	★	★	★
感应距离 <i>Reaction distance</i> (mm)		2 / 1	4 / 2	8 / 5	15 / 10
设定距离 <i>Setting distance</i> (mm)		0 to 1 / 1	0 to 3 / 1.5	0 to 7 / 4	0 to 12 / 8
工作电压 <i>Operating voltage</i>	<i>D C</i>	10 ~ 30 V/DC			
	<i>A C</i>	90~250 V / AC 50 / 60 HZ			
消耗电流 <i>Current consumption</i>	<i>D C</i>	≤ 15 mA			
	<i>A C</i>	≤ 4 mA			
可检出物体 <i>Sensing object</i>		Ferrous metals 铁			
距 差 <i>Differential travel</i>		≤ 10% max. of Sn			
泄漏电流 <i>Off. state leakage current</i>		AC type : 3mA DC type : 1.1mA			
安装方式 <i>Mounting</i>		Screw cap 螺帽			
反应频率 <i>Frequency response</i>		100Hz AC 15Hz			
输出容量 <i>Max. switching current</i>		≤ 200 mA			
正负极保护 <i>Inverse polarity proof</i>		Yes			
结构保护程度 <i>Degree of protection</i>		IP - 67			
动作指示灯 <i>Indicator</i>		红色操作指示灯 <i>Operation Indicator (Red)</i>			
操作温度 <i>Ambient operating temperature</i>		-20 ~ 70°C			
出力电压降 <i>Voltage drop</i>		2V max.			
外壳材质 <i>Housing material</i>		塑料 ABS, 铜 Brass			
电线长度 <i>Cable length</i>		PVC 2M			
重 量 <i>Weight ; Approx.</i>		50 g	60 g	70 g	120 g
外观尺寸 (单位mm) <i>Dimensions (Unit mm)</i>					