

FEP 鐵氟龍線 *FEP Teflon insulation wire*

導體: 鍍錫銅絞線

Conductor: Tin-plated copper strand wire

額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+150 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26/28 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -65~+200 °C

線規 *Wire Gauge*: 10/12/14/16/18/20/22/24/26

28/30/32/36 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -80~+150 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26/28 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+200 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26/28 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+150 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: NO

溫度範圍 *Temp. range*: -80~+200 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26/28 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -80~+200 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: NO

溫度範圍 *Temp. range*: -80~+200 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26/28 AWG



額定電壓 *Rated voltage*: NO

溫度範圍 *Temp. range*: -60~+105 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -60~+150 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+200 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



PFA 鐵氟龍線 *(PVC) PFA Teflon insulation wire*

導體: 鍍銀銅絞線

Conductor: silver-plated copper strand wire

額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+250 °C

線規 *Wire Gauge*: 10/12/14/16/18/20/22/24/26
28/30/32/36 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -60~+200 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -80~+250 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+250 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 150V

溫度範圍 *Temp. range*: -80~+250 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+200 °C

線規 *Wire Gauge*: 16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+250 °C

線規 *Wire Gauge*: 20/22/24/26/28/30/32 AWG



矽膠絕緣玻璃纖維線 *Silicone rubber Fiberglass weave wire*

導體: 鍍錫銅絞線

Conductor: Tin-plated copper strand wire

額定電壓 *Rated voltage*: 500V

溫度範圍 *Temp. range*: -60~+180 °C

線規 *Wire Gauge*: 5/7/10/13/16/18/20 AWG



額定電壓 *Rated voltage*: 500V

溫度範圍 *Temp. range*: -60~+200 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -60~+150 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26/28/30 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -60~+150 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -60~+200 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -60~+200 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26 AWG



矽膠絕緣電線 *Silicone rubber insulations wire*

導體: 鍍錫銅絞線

Conductor: Tin-plated copper strand wire

額定電壓 *Rated voltage*: 300V/500V

溫度範圍 *Temp. range*: -60~+200 °C

線規 *Wire Gauge*: 8/10/12/16/18/20/22/26/27 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -60~+150 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 300V

溫度範圍 *Temp. range*: -60~+150 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 500V

溫度範圍 *Temp. range*: -60~+200 °C

線規 *Wire Gauge*: 5/7/9/13/17 AWG



額定電壓 *Rated voltage*: 500V

溫度範圍 *Temp. range*: -60~+200 °C


線規 *Wire Gauge*: 7/10/14/16/17/18 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -60~+150 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26 AWG



額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -60~+150 °C

線規 *Wire Gauge*: 14/16/17/18/20/22/24/26 AWG



耐熱防火線 *300/500 °C Fire-resistant wire*

導體: 裸銅、鍍鎳銅絞線、純鎳絲絞線

Conductor: Nickel-plated copper strand wire

額定電壓 *Rated voltage*: 600V

溫度範圍 *Temp. range*: -80~+250 °C

線規 *Wire Gauge*: 10/12/14/16/18/20/22/24/26
28/30/32/36 AWG

