

型 號 <i>Model</i>		<i>E13091M1</i>	<i>E13091C2</i>	<i>E118665M</i>	<i>E11866C1</i>	<i>E13092M1</i>
外 觀 <i>Appearance</i>						
輸 出 方 式 <i>Output Control</i>	<i>DC type-NPN NO</i>	★	★	★	★	★
	<i>DC type-NPN NC</i>	★	★	★	★	★
	<i>DC type-NPN NO + NC</i>	★	★	★	★	★
	<i>DC type-PNP NO</i>	★	★	★	★	★
	<i>DC type-PNP NC</i>	★	★	★	★	★
	<i>DC type-PNP NO + NC</i>	★	★	★	★	★
	<i>AC type SCR NO</i>	★	★	★	★	★
	<i>AC type SCR NC</i>	★	★		★	★
	<i>AC type Relay NO</i>	★	★		★	★
	<i>AC type Relay NC</i>	★	★		★	★
	<i>AC type Relay NO + NC</i>	★	★			★
漫反射型	<i>Diffuse type distance</i>		20cm~100cm		10cm	
反饋反射	<i>Retro reflective distance</i>		3M~5M		2M	
對射型	<i>Through beam distance</i>	10M		5M		10M
工作電壓	<i>Operating voltage</i>	DC : 10-30 V AC : 90- 250 V				
消耗電流	<i>Current consumption</i>	DC < 15mA AC < 10mA				
輸出容量	<i>Max. switching current</i>	DC 200 mA AC 300 mA				
可檢出物體	<i>Sensing object</i>	透明或不透明體 <i>Transparent or Opaque Body</i>				
反應時間	<i>Response time</i>	DC < 2ms AC < 20ms				
指相角度	<i>Directional angle</i>	3° ~ 10°				
環境光度	<i>Environment luminosity</i>	太陽光10000LX以下 <i>Sunlight under 10000LX INCANDESCENT LAMP UNDER 3000LX</i>				
操作溫度	<i>Ambient operating temperature</i>	-20°C ~ 60°C				
結構保護程度	<i>Degree of protection</i>	IP - 66				
外殼材質	<i>Housing material</i>	塑料 <i>ABS</i> , 銅 <i>Brass</i>				
安裝方式	<i>Mounting</i>	螺帽 <i>Screw cap</i>	螺帽 <i>Screw cap</i>	螺帽 <i>Screw cap</i>	螺帽 <i>Screw cap</i>	螺帽 <i>Screw cap</i>
重 量	<i>Weight ; Approx.</i>					
外觀尺寸 (單位 mm) <i>Dimensions (Unit mm)</i>						