

型 號 <i>Model</i>		<i>PL125004</i>	<i>PL185008</i>	<i>PL305008</i>		
外 觀 <i>Appearance</i>						
輸 出 方 式 <i>Output Control</i>	<i>DC type-NPN NO</i>	★	★	★		
	<i>DC type-NPN NC</i>	★	★	★		
	<i>DC type-PNP NO</i>	★	★	★		
	<i>DC type-PNP NC</i>	★	★	★		
	<i>AC type 2 wires NO</i>	★	★	★		
	<i>AC type 2 wires NC</i>	★	★	★		
感應距離 <i>Reaction distance</i>		<i>4 mm</i>	<i>8 mm</i>	<i>15mm</i>		
設定距離 <i>Setting distance</i>		<i>0 to 3 mm</i>	<i>0 to 7 mm</i>	<i>0 to 12 mm</i>		
工作電壓 <i>Operating voltage</i>	<i>D C</i>	<i>10~30 V/DC</i>				
	<i>A C</i>	<i>90~250 V/AC 50/60 HZ</i>				
消耗電流 <i>Current consumption</i>	<i>D C</i>	<i>≤ 15 mA</i>				
	<i>A C</i>	<i>≤ 4 mA</i>				
可檢出物體 <i>Sensing object</i>		<i>Ferrous metals 鐵</i>				
距 差 <i>Differential travel</i>		<i>≤ 10% max. of Sn</i>				
洩漏電流 <i>Off. state leakage current</i>		<i>AC type : 3mA DC type : 1.1mA</i>				
安裝方式 <i>Mounting</i>		<i>Screw cap 螺帽</i>				
反應頻率 <i>Frequency response</i>		<i>300Hz AC 15Hz</i>	<i>100Hz AC 15Hz</i>			
輸出容量 <i>Max. switching current</i>		<i>≤ 200 mA</i>				
正負極保護 <i>Inverse polarity proof</i>		<i>Yes</i>				
結構保護程度 <i>Degree of protection</i>		<i>IP - 67</i>				
動作指示燈 <i>Indicator</i>		<i>紅色操作指示燈 Operation Indicator (Red)</i>				
操作溫度 <i>Ambient operating temperature</i>		<i>-20 ~ 70 °C</i>				
出力電壓降 <i>Voltage drop</i>		<i>2V max.</i>				
外殼材質 <i>Housing material</i>		<i>塑料 ABS, 銅 Brass</i>				
電線長度 <i>Cable length</i>		<i>PVC 2M</i>				
重 量 <i>Weight ; Approx.</i>		<i>100 g</i>	<i>110 g</i>	<i>150 g</i>		
外觀尺寸(單位 <i>mm</i>) <i>Dimensions (Unit mm)</i>						