

型 號 Model		E13091MI	E13091C2	E118665M	E11866CI	E13092MI
外觀 Appearance						
輸出方式 Output Control	DC type-NPN NO	*	*	*	*	*
	DC type-NPN NC	*	*	*	*	*
	DC type-NPN NO + NC	*	*	*	*	*
	DC type-PNP NO	*	*	*	*	*
	DC type-PNP NC	*	*	*	*	*
	DC type-PNP NO + NC	*	*	*	*	*
	AC type SCR NO	*	*	*	*	*
	AC type SCR NC	*	*		*	*
	AC type Relay NO	*	*		*	*
	AC type Relay NC	*	*		*	*
	AC type Relay NO + NC	*	*			*
漫反射型	Diffuse type distance		20cm~100cm		10cm	
反饋反射	Retro reflective distance		3M~5M		2M	
對射型	Through beam distance	10M		5M		10M
工作電壓	Operating voltage	DC : 10-30 V AC : 90- 250 V				
消耗電流	Current consumption	DC < 15mA AC < 10mA				
輸出容量	Max. switching current	DC 200 mA AC 300 mA				
可檢出物體	Sensing object	透明或不透明體 Transparent or Opaque Body				
反應時間	Response time	DC < 2ms AC < 20ms				
指相角度	Directional angle	3° ~ 10°				
環境光度	Environment luminosity	太陽光10000LX以下 Sunlight under 10000LX INCANDESCENT LAMP UNDER 3000LX				
操作溫度	Ambient operating temperature	-20°C ~ 60°C				
結構保護程度	Degree of protection	IP 66				
外殼材質	Housing material	塑料 ABS, 銅 Brass				
安裝方式	Mounting	螺帽 Screw cap	螺帽 Screw cap	螺帽 Screw cap	螺帽 Screw cap	螺帽 Screw cap
重 量	Weight ; Approx.					
外觀尺寸 (單位 mm) Dimensions (Unit mm)						