



## 型號索引 ORDERING CODE

系列 Series	<b>N</b>	產品系列區分 Series Product
	<b>C</b>	P: 電感 C: 電容 H: 霍爾
樣式 Type	<b>P</b>	1: 圓柱平頭 2: 圓柱插接 3: 方型
	<b>1</b>	4: 圓柱凸頭
		P: Inductive C: Capacitive H: Hall
直徑/寬 Diameter/Width	<b>0</b>	1: Round Shielded 2: Round Quick-Disconnect
	<b>6</b>	3: Rectangular 4: Round Unshielded
		08: 8mm 12: 12mm 18: 18mm
長度 Length	<b>5</b>	
	<b>2</b>	35: 35mm 50: 50mm
距離 Distance	<b>0</b>	
	<b>1</b>	01: 1mm 10: 10mm
輸出方式 Output	<b>A</b>	A: AC D: DC
	<b>A</b>	A: A接點(常開) B: B接點(常閉)
	<b>N</b>	A: Normal Open B: Normal Close
		P: PNP N: NPN R: Relay
線長 Cordset length	<b>1</b>	
	<b>0</b>	01: 1M 10: 10M
出線 Wire	<b>3</b>	3: 3線式(3 wires) 4: 4線式(4 wires)
工作電壓 Voltage	<b>1</b>	11A: 110V/AC 22A: 220V/AC
	<b>1</b>	A36: 36V/AC
	<b>A</b>	D12: 12V/DC D30: D30V/DC
其他 Other		其他特別規格 Other

### 結構保護等級 GRADE OF PROTECTION:

保護程度	Protective Grade
防霧型 vapor resistant	無論從那方向來的水沫都不會造成損壞 Not affected by water bubbles from all directions.
防噴流型 water splash resistant	不論從那個方向來的,直接噴水也不受影響的 Not affected by water splash from all directions.
防水型 water tight	在一定壓力下直接噴水,內部也不會進水的 No penetration by direct water spray from all directions under specific water pressure.
防滲入型 resistant	在設定的水壓條件,放入水中內部而不進水,歷時三十分鐘 No penetration by water ever when the object is submerged in the water for 30 minutes.
水中型 submersible article	可以在指定壓力的水中,長時間使用的開關 Objects which can be used for a long period of time in the water under a specific water pressure.
耐塵型 endure dust	可以在指定粉塵環境中,正常動作 Can work normally in a specific dusty place.

### 各種金屬或鍍層造成影響,須加以確認 The influence of various metals and cladding

#### 材料 Material

鐵 Iron	100%
不銹鋼 Stainless Steel	60%
黃銅 Brass	40%
鋁 Aluminum	30%
銅 Copper	20%

### 使用動作名詞說明 Description of Action

