

型 號 <i>Model</i>		<i>Pa305015</i>	<i>PWIPA0023</i>	<i>PWIPA0024</i>	<i>PWIPa0023</i>	<i>PWIPa0024</i>
外 觀 <i>Appearance</i>						
輸 出 方 式 <i>Output Control</i>	<i>DC type-NPN NO</i>	✱				
	<i>DC type-NPN NC</i>	✱				
	<i>DC type-PNP NO</i>	✱				
	<i>DC type-PNP NC</i>	✱				
	<i>AC type 2 wires NO</i>	✱				
	<i>AC type 2 wires NC</i>	✱				
感應距離 <i>Reaction distance</i>		15 mm				
設定距離 <i>Setting distance</i>		0 to 12 mm				
工作電壓 <i>Operating voltage</i>		<i>D C</i>	10~30 V/DC			
		<i>A C</i>	90~250 V/AC 50/60 HZ			
消耗電流 <i>Current consumption</i>		<i>D C</i>	≤ 15 mA			
		<i>A C</i>	≤ 4 mA			
可檢出物體 <i>Sensing object</i>		Ferrous metals 鐵				
距 差 <i>Differential travel</i>		≤ 10% max. of Sn				
洩漏電流 <i>Off. state leakage current</i>		AC type : 3mA DC type : 1.1mA				
安裝方式 <i>Mounting</i>		Screw cap 螺帽				
反應頻率 <i>Frequency response</i>		300Hz AC 15Hz	100Hz AC 15Hz			
輸出容量 <i>Max. switching current</i>		≤ 200 mA				
正負極保護 <i>Inverse polarity proof</i>		Yes				
結構保護程度 <i>Degree of protection</i>		IP - 67				
動作指示燈 <i>Indicator</i>		紅色操作指示燈 Operation Indicator (Red)				
操作溫度 <i>Ambient operating temperature</i>		-20 ~ 70 °C				
出力電壓降 <i>Voltage drop</i>		2V max.				
外殼材質 <i>Housing material</i>		塑料 ABS, 銅 Brass				
電線長度 <i>Cable length</i>		PVC 2M				
重 量 <i>Weight ; Approx.</i>		150 g				
外觀尺寸 (單位 mm) <i>Dimensions (Unit mm)</i>						